

Podnośniki jednołożkowe – specyfikacja

Nr. art.	Model	Udźwig (kg) *	Wymiary platformy (mm)	Wysokość ponoszenia (mm)	Min. wysokość (mm)	Czas podnoszenia (s)	Silnik (kW)	Waga (kg)
40001	SPX-5/60-1C	500	950x600	600	180	8	0,8	120
40002	SPX-5/82-1C	500	1350x800	820	180	12	0,8	170
40031	SPX-5/82-1C	500	1350x1000	820	180	12	0,8	185
40014	SPX-5/82-1C	500	1500x1000	820	180	12	0,8	200
40013	SPX-10/60-1C	1000	950x600	600	180	14	0,8	145
42501	ECO-10/82-1C #	1000	1200x800	820	180	18	0,8	175
40003	SPX-10/82-1C	1000	1350x800	820	180	21	0,8	185
40032	SPX-10/82-1C	1000	1350x1000	820	180	21	0,8	200
40004	SPX-10/82-1C	1000	1500x1000	820	180	21	0,8	215
40021	SPX-10/110-1C	1000	1700x900	1100	230	33	0,8	320
40022	SPX-10/110-1C	1000	2000x1000	1100	230	33	0,8	340
40020	SPX-10/130-1C	1000	2000x1000	1300	230	33	0,8	360
40005	SPX-15/82-2C	1500	1350x800	820	230	24	0,8	215
40033	SPX-15/82-2C	1500	1350x1000	820	230	24	0,8	225
40006	SPX-15/82-2C	1500	1500x1000	820	230	24	0,8	230
40023	SPX-15/110-2C	1500	1700x900	1100	230	38	0,8	330
40024	SPX-15/110-2C	1500	2000x1000	1100	230	38	0,8	350
40007	SPX-20/82-2C	2000	1350x800	820	230	42	0,8	215
40034	SPX-20/82-2C	2000	1350x1000	820	230	42	0,8	225
40008	SPX-20/82-2C	2000	1500x1000	820	230	42	0,8	230
40025	SPX-20/110-2C	2000	1700x900	1100	230	68	0,8	330
40026	SPX-20/110-2C	2000	2000x1000	1100	230	68	0,8	350
40036	SPX-20/130-2C	2000	2000x1000	1300	260	22	2,3	370
40041	SPX-20/160-2C	2000	2200x1200	1600	300	33	2,3	470
40042	SPX-20/160-2C	2000	2200x1500	1600	300	33	2,3	520
40051	SPX-20/180-2C	2000	3000x1200	1800	300	36	2,3	590
40052	SPX-20/180-2C	2000	3000x1500	1800	300	36	2,3	630
40009	SPX-30/82-2C	3000	1350x800	820	250	18	2,3	265
40035	SPX-30/82-2C	3000	1350x1000	820	250	18	2,3	295
40010	SPX-30/82-2C	3000	1500x1000	820	250	18	2,3	325
40027	SPX-30/110-2C	3000	1700x900	1100	260	28	2,3	360
40028	SPX-30/110-2C	3000	2000x1000	1100	260	28	2,3	380
40037	SPX-30/130-2C	3000	2000x1200	1300	300	28	2,3	430
40043	SPX-30/160-2C	3000	2200x1200	1600	300	42	2,3	490
40044	SPX-30/160-2C	3000	2200x1500	1600	300	42	2,3	540
40053	SPX-30/180-2C	3000	3000x1200	1800	300	45	2,3	800
40054	SPX-30/180-2C	3000	3000x1500	1800	300	45	2,3	850
40011	SPX-40/82-3C	4000	1350x800	820	300	27	2,3	300
40012	SPX-40/82-3C	4000	1500x1000	820	300	27	2,3	360
40029	SPX-40/110-3C	4000	1700x900	1100	300	32	3,5	405
40030	SPX-40/110-3C	4000	2000x1000	1100	300	32	3,5	425
40038	SPX-40/130-3C	4000	2000x1200	1300	300	32	3,5	490
40046	SPX-40/160-3C	4000	2200x1200	1600	350	47	3,5	540
40047	SPX-40/160-3C	4000	2200x1500	1600	350	47	3,5	590
40055	SPX-40/180-3C	4000	3000x1200	1800	400	51	3,5	870
40056	SPX-40/180-3C	4000	3000x1500	1800	400	51	3,5	1070
40057	SPX-50/110-4C	5000	2000x1200	1100	400	34	3,5	850

40039	SPX-50/130-4C	5000	2200x1200	1300	400	34	3,5	870
40058	SPX-50/160-4C	5000	2500x1200	1600	400	49	3,5	900
40059	SPX-50/160-4C	5000	2500x1500	1600	400	49	3,5	950
40060	SPX-50/180-4C	5000	3000x1200	1800	400	54	3,5	1000
40061	SPX-50/180-4C	5000	3000x1500	1800	400	54	3,5	1050
40062	SPX-60/110-4C	6000	2000x1200	1100	400	43	3,5	900
40040	SPX-60/130-4C	6000	2200x1200	1300	400	43	3,5	930
40063	SPX-60/160-4C	6000	2500x1200	1600	400	62	3,5	1000
40064	SPX-60/160-4C	6000	2500x1500	1600	400	62	3,5	1050
40065	SPX-60/180-4C	6000	3000x1200	1800	400	68	3,5	1200
40066	SPX-60/180-4C	6000	3000x1500	1800	400	68	3,5	1300
40067	SPX-80/150-6C	8000	3000x2000	1500	600	49	5,5	1850
40068	SPX-100/150-6C	10000	3000x2000	1500	600	62	5,5	1900

*) Warunkuje równe rozłożenie ładunku

) Dostawa jedynie w wykonaniu standardowym