

Podnośniki dwu- nożycowe poziome

Nr. art.	Model	Udźwig (kg) *	Wymiary platformy (mm)	Wysokość ponoszenia (mm)	Min. wysokość (mm)	Czas podnoszenia (s)	Silnik (kW)	Waga (kg)
40206	SPXX-10/82-2C	1000	2700x800	820	230	23	0,8	320
40207	SPXX-10/110-2C	1000	3400x900	1100	230	38	0,8	580
40208	SPXX-10/160-4C	1000	4400x1200	1600	300	37	2,3	800
40201	SPXX-20/82-2C	2000	2700x800	820	230	42	0,8	330
40211	SPXX-20/110-2C	2000	3400x900	1100	230	68	0,8	600
40221	SPXX-20/160-4C	2000	4400x1200	1600	300	37	2,3	900
40202	SPXX-30/82-4C	3000	2700x800	820	260	28	2,3	390
40212	SPXX-30/110-4C	3000	3400x900	1100	260	45	2,3	620
40222	SPXX-30/160-4C	3000	4400x1200	1600	300	66	2,3	920
40203	SPXX-40/82-4C	4000	2700x800	820	260	28	2,3	390
40213	SPXX-40/110-4C	4000	3400x900	1100	260	45	2,3	620
40223	SPXX-40/160-4C	4000	4400x1200	1600	300	66	2,3	950
40204	SPXX-60/82-4C	6000	2700x800	820	260	27	3,5	490
40214	SPXX-60/110-6C	6000	3400x900	1100	300	50	3,5	680
40224	SPXX-60/160-4C	6000	4400x1200	1600	300	62	3,5	1090
40225	SPXX-60/160-4C	6000	5000x1500	1600	300	62	3,5	1420
40226	SPXX-60/160-4C	6000	6000x2000	1600	300	62	3,5	1560
40205	SPXX-80/82-6C	8000	2700x800	820	300	40	3,5	560
40215	SPXX-80/110-6C	8000	3400x900	1100	300	65	3,5	770
40227	SPXX-80/160-6C	8000	4400x1200	1600	350	62	5,5	1600
40228	SPXX-80/160-6C	8000	5000x1500	1600	350	62	5,5	1750
40229	SPXX-80/160-6C	8000	6000x2000	1600	350	62	5,5	1860

*) Warunkuje równe rozłożenie ładunku