

## Podnośniki nisko profilowe typu "U"

Nr. art.	Model	Udźwig (kg) *	Wymiary platformy (mm)	Wysokość ponoszenia (mm)	W stanie złożonym (mm)	Czas podnoszenia (s)	Silnik (kW)	Waga (kg)
40301	SPXL-5/63-2C	500	950x600	630	80	9	0,8	120
40311	SPXL-6/78-2C	600	1500x800	800	80	18	0,8	210
40318	SPXL-6/78-2C	600	1500x1000	800	80	18	0,8	230
40321	SPXL-6/97-2C	600	1610x800	970	80	18	0,8	210
40312	SPXL-10/78-2C	1000	1500x800	800	80	18	0,8	290
40320	SPXL-10/78-2C	1000	1500x1000	800	80	18	0,8	310
40322	SPXL-10/97-2C	1000	1610x800	970	80	18	0,8	290
40314	SPXL-15/78-3C	1500	1500x800	800	80	27	0,8	340
40329	SPXL-15/78-3C	1500	1500x1000	800	80	27	0,8	360
40311	SPXL-15/97-3C	1500	1610x800	970	80	27	0,8	340
40316	SPXL-20/78-4C	2000	1500x800	800	100	36	0,8	380
40331	SPXL-20/78-4C	2000	1500x1000	800	100	36	0,8	400
40326	SPXL-20/97-4C	2000	1610x800	970	100	36	0,8	380
40401	SPXUS-6/78-2C	600	1500x1100	800	80	18	0,8	210
40411	SPXUS-6/97-2C	600	1610x1100	970	80	18	0,8	210
40402	SPXUS-10/78-2C	1000	1500x1100	800	80	18	0,8	270
40403	SPXU-10/78-2C **	1000	1610x1100	800	80	18	0,8	270
40412	SPXUS-10/97-2C	1000	1610x1100	970	80	18	0,8	270
40404	SPXUS-15/78-4C	1500	1500x1300	800	100	36	0,8	310
40405	SPXU-15/78-4C **	1500	1610x1300	800	100	36	0,8	310
40413	SPXUS-15/97-4C	1500	1610x1300	970	100	36	0,8	310
40406	SPXUS-20/78-4C	2000	1500x1300	800	100	36	0,8	310
40407	SPXU-20/78-4C **	2000	1610x1300	800	100	36	0,8	310
40414	SPXUS-20/97-4C	2000	1610x1300	970	100	36	0,8	310

\* ) Warunkuje równe rozłożenie ładunku

\*\* ) Wbudowany agregat hydrauliczny